



RHFA Sweeper

For 3 point Category I or II 3 point hitch tractors

FEATURES:

- 5', 6', or 8' widths available
- Rear mounted, mechanical drive sweeper sweeps forward & backwards
- Designed for grounds maintenance applications
- 30° manual angling or optional hydraulic angling
- 6 to 8ft by 32" diameter brushes
- Optional sprinkler systems and storage stands available
- Attaches to Category I or II 3 point hitches on the front or rear of tractors
- T-shaft gear box turns over to change brush rotation from forward to backward



PALADIN LIGHT CONSTRUCTION

Distributed by: J. S. Woodhouse Co., Inc.
1314 Union St
West Springfield, MA 01089

Phone: 413-739-5607
Fax: 413-732-3786
email: info@jswoodhouse.com
website: www.jswoodhouse.com

RHFA Sweepers

STANARD FEATURES:

Brush Drive

- Brush powered by 540 RPM PTO
- Power Transmitted from gearbox to brush by telescoping constant velocity drive shaft

Mounting

- Mounts to ASAE Category I or II 3 point hitch on the front or rear
- Category I pins included and Category II pins are available

Brush

- 6ft (1.8m) by 32" (81.3cm) diameter sectional brush
- Choice of bristle material poly, wire, or poly/wire sets
- Designed for 10" (25.4cm) I.D. water type brush segments
- Detachable brush hood covers 120° of brush and ends

Brush Controls

- Manual angle change 30° to left & right
- Brush speed controlled by vehicle's engine
- Plate swing standard
- Pressure adjusted by changing position of spring/chains
- Lift sweeper by raising tractor arms

Storage Stands

- Four permanent stands protect brush during storage

OPTIONAL FEATURES:

Brush Widths

- 5', 6' or 8' widths available

Hydraulic Angle Change

- Hydraulic cylinder angles sweeper 30° left and right

- Cylinder, hoses and mounting brackets included

- Activating valve not included

Auxiliary Valve

- Extra valve to operate sweeper lift or swing

180° Brush Hood

Dirt Deflector

- For 120° or 180° brush hoods and rear mounting units, attaches under framework between tractor & sweeper

Sprinkler System

- Spray bar mounts on brush hood and supplies a fine curtain of water across face of brush reducing dust
- Includes electric pump, hoses, spray nozzles and bar
- 25 gallon (95 L) water tank available for customer to install

Specifications

Width Standard 7 ft brush	84"
Sweeping Path	71"
Weight (lbs)	1,000

Distributed by: J. S. Woodhouse Co., Inc.
1314 Union St
West Springfield, MA 01089

Phone: 413-739-5607
Fax: 413-732-3786
email: info@jswoodhouse.com
website: www.jswoodhouse.com