



WOODY MANURE SPREADERS

2500 and 3300 MODELS
AGRICULTURAL APPLICATION



Woody Equipment

Woody Equipment designs and manufactures robust and high quality forestry and agricultural equipment.

Designed and manufactured in Quebec

equipementswoody.com

Our spreaders are equipped with a closed oil bath and equipped with a grade H chain, a sealed gear box, a shear bolt, a double PTO seal, rear directional LED lights, a unique and unmatched steel treatment before the paint application, an epoxy primer and a urethane paint. The central screw is equipped with two cylinders allowing it to move vertically in the tank and the evacuation device is equipped with reversible and interchangeable CHT 400 steel fingers.

equipementswoody.com

WOODY MANURE SPREADERS



TECHNICAL SPECIFICATIONS - WOODY MANURE SPREADERS

MODEL	2500	3300
RECOMMENDED VEHICLE	125 hp +	150 hp +
Loading capacity in gallons with lateral sides	2500	3300
Overall length	21'7"	21'7"
Tank length X width	16' x 7'4"	16' x 8'4"
Loading height with lateral sides	7'8"	8'9"
Tank steel thickness	3/16"	3/16"
Tandem axial	yes	yes
Wheel hub diameter	4"	4"
Wheel hub capacity	16 000 lb	16 000 lb
Tire size (standard) (optional)	550-45-22.5, 16-ply 600-55-22.5, 16-ply	600-55-22.5, 16-ply ---
Power take-off (PTO) input speed	1 000 rpm	1 000 rpm
Auger speed	25 rpm	25 rpm
Discharge system speed	900 rpm	900 rpm
Discharge system diameter	18"	18"
Side discharge width	45"	45"
Weight without wheels	6 500 lb	8 400 lb
Total weight	7 800 lb	10 000 lb



V1.20170223-EN – Designed by Expressions Grafik

WOODY EQUIPMENT INC.
205 rue Commerciale, Saint-Odilon (QC) G0S 3A0
T. 418 464-2748 | F. 418 464-2746
info@equipementswoody.com

