

MILLCREEK TOPDRESSERS

THE PREFERRED CHOICE
OF TURF PROFESSIONALS



MILLCREEK
MANUFACTURING CO
Spreaders for the Earth's
Farms, Fields, and Turf

Distributed by: J. S. Woodhouse Co., Inc.
1314 Union St
West Springfield, MA 01089

Phone: 413-739-5607
Fax: 413-732-3786
email: info@jswoodhouse.com
website: www.jswoodhouse.com

THE PREFERRED CHOICE OF SPORTS TURF AND GOLF COURSE PROFESSIONALS



Generous Load Capacity
3.2 cubic yards heaped capacity; optional extension sides available.

Large 7500 lb. Payload
Allows fewer trips, fewer loads.

Dual Hydraulic Controls
Provide infinite speed adjustments for belt and attachment(s).

Powerful Hydraulic Drive System
Standard tractor hydraulics OR PTO driven hydraulics.

Rubber Coated Drive Rollers
Prevent belt slippage.

Flotation Turf Tires
Provide low ground pressure and wide track stability.

Self-aligning V-Track System
Keeps the material delivery belt aligned.

Saber Tooth™ Beater
Spreads any material, wet or dry; 8 to 12 ft. wide spread pattern. Alternate spreading attachments include Dual Spinners, a Rear Cross Conveyor, and a 42" wide Brush. (Each attachment purchased separately.)

Available for the Turf Tiger™: optional precision apron control.

THE AFFORDABLE SOLUTION FOR TURF CARE



Loading Flares
Simplify loading.

Choose Your Capacity
Two models available—1.8 or 2.3 cubic yard heaped capacity.

Drive System
Simple, heavy-duty drive components are more reliable.

Standard PTO Hookup

Apron Conveyor
Exclusive design for guaranteed tracking and no slipping.

Metering Gate
Easily adjusts for high/low volume material flow.

Saber Tooth Beater
Spreads various textured materials—even wet, damp, or clumpy. Up to 8 ft. wide spread pattern; from a dusting up to one inch per pass.

Great new Turf Tiger Cub Options: Model 3100 Engine Drive, as an alternate to the standard PTO model, and the Path Maker attachment for laying down materials along nature trails or walking paths.

LEARN MORE AT WWW.MILLCREEKMFG.COM

TURF EQUIPMENT DESIGNED WITH YOU IN MIND

Your turf, your way. What a concept!

Versatile Millcreek turf equipment is really all about you—what you need, when you need it, to get the job done. We get it—time is money. So, in the interests of saving you both, we've engineered every detail in our topdressers to maximize performance and protect against breakdowns.

You need equipment that will spread a variety of materials in a variety of conditions. DONE.

You need equipment that will work, day in and day out, to establish, restore, revitalize. DONE.

You need it to be easy. DONE.

You need it to be affordable. DONE.

Whether you care for landscaping, sports fields, golf courses, or parks, there's a Millcreek turf topdresser with your name on it. What are you waiting for? Let's get it done together.



Distributed by: J. S. Woodhouse Co., Inc.
1314 Union St
West Springfield, MA 01089

Phone: 413-739-5607
Fax: 413-732-3786
email: info@jswoodhouse.com
website: www.jswoodhouse.com

MILLCREEK COMMERCIAL AERATORS



BACK TO THE BASICS WITH MILLCREEK'S COMMERCIAL AERATORS

Aeration and topdressing go hand in hand—that's "Turf 101". And that's also why Millcreek's Commercial Aerators are the perfect partner for our family of topdressers. Versatile, affordable, rugged, built to last. We're sure we have an aerator model to suit your application to a "T"—choose from three frame sizes, two hitch styles, and two aeration options (spoons, for standard core plug aeration, or slicing blades).

Learn more at www.millcreekmfg.com.

TOPDRESSER SPECIFICATIONS

	MODEL 3100	MODEL 3200	MODEL 4300
Capacity, Struck	1.0 yd ³ /8 m ³	1.3 yd ³ /1 m ³	2.2 yd ³ /1.7 m ³ (1)
Capacity, Heaped	1.8 yd ³ /1.4 m ³	2.3 yd ³ /1.8 m ³	3.2 yd ³ /2.4 m ³ (1)
Capacity, Weight	3000 lbs/1361 kg	3750 lbs/1701 kg	7500 lbs/3375 kg
Body length	89.5 in/2.2 m	114 in/2.9 m	84 in/2.1 m
Body width	37 in/94 cm	37 in/94 cm	48 in/1.2 m
Body height	17.5 in/44.5 cm	17.5 in/44.5 cm	24 in/61 cm
Overall length	11 ¹ / ₂ /3.4 m	13 ¹ / ₄ m	12 ⁸ / ₈ /3.8 m
Overall width	70 in/1.8 m	70 in/1.8 m	93 in/2.3 m
Overall height	51 in/1.3 m	51 in/1.3 m	73 in/1.8 m
Loading height	43 in/1.1 m	43 in/1.1 m	65 in/1.6 m
Construction	All Steel (13 gauge) with Poly Floor	All Steel (13-gauge) with Poly Floor	11-gauge steel body on heavy steel chassis
Apron Conveyor	67# Steel detachable chain	67# Steel detachable chain	3/16" (thick) black PVC belt
Tires	Turf (26.4 x 14 x 12, 4 ply) Ground Pressure, loaded 18 PSI	Turf (26.4 x 14 x 12, 4 ply) Ground Pressure, loaded 19 PSI	Turf 41/18LL-16.1, 6-ply Ground Pressure, loaded 14 PSI
Beater Bearing	Sealed ball bearings	Sealed ball bearings	Sealed ball bearings
Beater Drive	Gear box/Chain	Gear box/Chain	Hydraulic motor
Apron Drive	Gear box/Chain reduction	Gear box/Chain reduction	Hydraulic motor/Chain reduction
Weight (with tires)	1140 lbs/517 kg	1300 lbs/590 kg	2180 lbs/981 kg
Tractor Weight and HP required	2000 lbs/907 kg 25 HP & greater	2250 lbs/1021 kg 30 HP & greater	35 HP & greater, tractor weight must be at least 50% of gross loaded weight.

NOTE: Optional extension sides further extend the capacity; maximum payload of 7500 lbs. must not be exceeded.



Distributed by: J. S. Woodhouse Co., Inc.
1314 Union St
West Springfield, MA 01089

Phone: 413-739-5607
Fax: 413-732-3786
email: info@jswoodhouse.com
website: www.jswoodhouse.com