

Worksaver.

**Designed.
Engineered.
Remarkable
Value.**



Model 580 Mixer

**Ideal for mixing feed, fertilizer, inoculating seed,
potting soil and other mixing jobs.**



Distributed by: J. S. Woodhouse Co., Inc.
1314 Union St
West Springfield, MA 01089

Phone: 413-739-5607
Fax: 413-732-3786
email: info@jswoodhouse.com
website: www.jswoodhouse.com

Worksaver Model 580 Mixer

- Two piece steel drum construction with internal paddles for uniform mixing and clean dumping.
- Compact, trouble free, long life design with few moving parts.
- Ideal for mixing feed, fertilizer, inoculating seed, potting soil and other mixing jobs.
- Five (5) cu./ft. capacity (1 bag mix).
- Hydraulic top link cylinder provides positive dump control.
- Parking stand for easy storage.
- Number 40-roller chain drives mixing drum.
- Adjustable Cat. I hitch allows easy hook up to most tractors (7/8 Dia. Lift pins).
- Sealed ball bearings provide long service life with reduced maintenance.

Capacity	Five (5) cu./ft. (1 bag mix)
Drum opening (in/mm)	17.5 / (444 mm)
Overall drum length (in/mm)	32 / (812 mm)
Diameter of drum (in/mm)	32 / (812 mm)
Drum construction	2-piece bolted
Drum thickness	11-gauge steel
Cone thickness	14-gauge steel
Drive system	Tractor PTO
PTO driveline	Metric Series I
PTO speed	540 rpm
Drum drive	#40 chain
Drive ratio	8.77:1
Shield PTO drive	Standard
Chain tighter	Standard
Bearing type	Sealed ball bearings
Hydraulic topline cylinder	Standard (Double Acting)
Cylinder size (in/mm)	1.75 (44 mm) x 13 (330 mm)
Hitch requirement	Cat. I (7/8" Dia. Lift pins)
Hydraulic topline positions	Three (3)
Lower pull pin positions	Four (4)
Parking stands	Standard
Tractor requirement (min. PTO HP)	25 PTO HP*
Shipping weight (lb/kg)	253 / (115 kg)
Product Computer Number	780620

*Be sure front of tractor is properly counterbalanced w/ front-end weights.

**Be sure front of tractor is properly counterbalanced with front-end weights or front-end loader.*

**Designed.
Engineered.
Remarkable
Value.**



READ AND UNDERSTAND OPERATOR'S MANUAL BEFORE OPERATION.



FULL MIXER WILL PUT A HEAVY LOAD ON THE REAR OF YOUR TRACTOR. BE SURE FRONT OF TRACTOR IS PROPERLY COUNTERBALANCED WITH WEIGHTS.



NEVER ALLOW CHILDREN OR BYSTANDERS AROUND TRACTOR OR MIXER WHEN YOU ARE USING EQUIPMENT.

Worksaver Inc. has a corporate policy of continuous product improvement and development; therefore, specifications are subject to change without any advance notice. Worksaver Inc. is not responsible for differences between specifications or illustrations contained in this publication and the actual equipment.

Distributed by: J. S. Woodhouse Co., Inc.
1314 Union St
West Springfield, MA 01089

Phone: 413-739-5607
Fax: 413-732-3786
email: info@jswoodhouse.com
website: www.jswoodhouse.com