

Work saver.

**Designed.
Engineered.
Remarkable
Value.**



Tandem Disc Harrows

Ideal for fine finish seedbeds, discs under light cover material. Main frame design incorporates strength and rigidity to work in tough conditions.



Distributed by: J. S. Woodhouse Co., Inc.
1314 Union St
West Springfield, MA 01089

Phone: 413-739-5607
Fax: 413-732-3786
email: info@jswoodhouse.com
website: www.jswoodhouse.com

Worksaver Tandem Disc Harrows

- Engineered simplicity with opposed action disc gangs. Frame design angles disc gangs to eliminate problem of blade overlap and uncut soil.
- Cast iron bearing caps & spools with grease fittings provide long service life.
- Solid 1-inch steel axles & heavy cast spools add weight to the disc gangs for penetration.
- Optional weight frame (# 940325) allows additional weight to be added easily when required.
- High carbon steel disc blades provide excellent cutting.
- 7-1/4" blade spacing produces fine texture level finish.

TANDEM DISC HARROW SPECIFICATIONS

Model No.	Width (ft.)	Blade Type	# of Blades	Blade Diameter	Item No.	Weight (lbs.)
DH-55-16P	5-1/2 ft.	Plain	16	16"	940354	374 lbs.
DH-55-16N	5-1/2 ft.	Notched	16	16"	940352	362 lbs.
DH-55-16C	5-1/2 ft.	Combination	16	16"	940350	368 lbs.
DH-65-16P	6-1/2 ft.	Plain	20	16"	940364	474 lbs.
DH-65-16N	6-1/2 ft.	Notched	20	16"	940362	462 lbs.
DH-65-16C	6-1/2 ft.	Combination	20	16"	940360	468 lbs.
DH-55-18P	5-1/2 ft.	Plain	16	18"	940359	445 lbs.
DH-55-18N	5-1/2 ft.	Notched	16	18"	940357	440 lbs.
DH-55-18C	5-1/2 ft.	Combination	16	18"	940355	435 lbs.
DH-65-18P	6-1/2 ft.	Plain	20	18"	940369	545 lbs.
DH-65-18N	6-1/2 ft.	Plain	20	18"	940367	540 lbs.
DH-65-18C	6-1/2 ft.	Plain	20	18"	940365	535 lbs.

**Be sure front of tractor is properly counterbalanced with front-end weights or front-end loader.*



READ AND UNDERSTAND OPERATOR'S MANUAL BEFORE OPERATION.



BE SURE FRONT OF TRACTOR IS PROPERLY COUNTERBALANCED WITH WEIGHTS.



NEVER ALLOW CHILDREN OR BYSTANDERS AROUND TRACTOR OR DISC WHEN YOU ARE USING EQUIPMENT.

Worksaver Inc. has a corporate policy of continuous product improvement and development; therefore, specifications are subject to change without any advance notice. Worksaver Inc. is not responsible for differences between specifications or illustrations contained in this publication and the actual equipment.

Distributed by: J. S. Woodhouse Co., Inc.
1314 Union St
West Springfield, MA 01089

Phone: 413-739-5607
Fax: 413-732-3786
email: info@jswoodhouse.com
website: www.jswoodhouse.com