

Work saver.

**Designed.
Engineered.
Remarkable
Value.**



WORKSAVER®

SmoothCut PTO Powered Stump Grinders

Economical and Efficient PTO powered stump grinder, makes stump removal fast and easy. Operator easily controls the stump grinder from the comfort of the tractor seat.



Distributed by: J. S. Woodhouse Co., Inc.
1314 Union St
West Springfield, MA 01089

Phone: 413-739-5607
Fax: 413-732-3786
email: info@jswoodhouse.com
website: www.jswoodhouse.com

Worksaver SmoothCut Stump Grinders

- Maneuverable - goes anywhere a tractor can; gets into tight places.
- Higher productivity via it's unique cutting wheel design.
- Cutting wheel design provides a smoother cutting action.
- Easy to operate - hydraulic controls allow easy operation from the tractor seat using existing tractor hydraulic controls.
- Durable carbide-tipped cutting teeth are economical and easy to replace.
- Harden bushings used in major pivot points for increased reliability.
- Grease zerks provided at major pivot points for extended service life.
- Standard needle valve for precise control of cutting feed rate for best cutting action.
- SureFoot stabilizer bar provides solid footing during operation.
- Rubber deflector helps controls chips and debris during grinding.
- Parking stand for easy storage.

SmoothCut Specifications

	Model SG-26	Model SG-36
Hitch	Cat. I	Cat. I/II
Overall length (est.)	75-inches	80-inches
PTO driveline type	Series 5	Series 6
PTO speed	----- 540 rpm -----	
Driveline protection	----- Slip Clutch -----	
Gearbox rating / ratio	60 hp / 1:1.5	100 hp / 1:1.46
Cutting wheel construction	-- Welded 2-piece laminated steel --	
Cutting wheel thickness	----- 3/4inch -----	
Cutting wheel diameter	26-inches	36-inches
Cutting wheel speed (approx.)	801 rpm	788 rpm
	5,515 ft./min	7430 ft./min
Number of teeth	30	39
Cutting teeth construction	----- Carbide steel bolt in -----	
Cutting height above ground	18-inches	18-inches
Cutting depth below ground	10-inches	10-inches
Max. cut depth per pass	5-inches	8-inches
Maximum horizontal cut	28-inches	33-inches
Swing arc	45-degrees	45-degrees
Minimum HP requirement	22-PTO hp	45-PTO hp
Maximum HP	50-PTO hp	100-PTO hp
Weight (est.)	660-lbs.	880-lbs.
Computer product number	811500	811550

**Be sure front of tractor is properly counterbalanced with front-end weights or front-end loader.*



READ AND UNDERSTAND OPERATOR'S MANUAL BEFORE OPERATION.



STUMP GRINDER WILL PUT A HEAVY LOAD ON THE REAR OF YOUR TRACTOR. BE SURE FRONT OF TRACTOR IS PROPERLY COUNTERBALANCED WITH WEIGHTS.



NEVER ALLOW CHILDREN OR BYSTANDERS AROUND TRACTOR OR STUMP GRINDER WHEN YOU ARE USING EQUIPMENT.

Worksaver Inc. has a corporate policy of continuous product improvement and development; therefore, specifications are subject to change without any advance notice. Worksaver Inc. is not responsible for differences between specifications or illustrations contained in this publication and the actual equipment.

Distributed by: J. S. Woodhouse Co., Inc.
1314 Union St
West Springfield, MA 01089

Phone: 413-739-5607
Fax: 413-732-3786
email: info@jswoodhouse.com
website: www.jswoodhouse.com